AZUMI READER **7465** SKU 1142034

astro



PRODUCT SPECIFICATION

GENERAL

| FINISH: | Matt Nickel | CABLE LENGTH: | Not Applicable |
|---------------------------|-------------------------|----------------------------|---|
| MAIN MATERIAL: | Metal - Zinc | GROSS WEIGHT: | 1.5 (kg) |
| DIMENSIONS: | H:212mm W:120mm D:158mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical | IP RATING: | IP20 |
| CUT OUT HOLE: | Not Applicable | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | Not Applicable | VOLTAGE: | Mains 230v |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Suitable for mounting on flammable material |
| MAIN LAMP | | | |
| LIGHT SOURCE: | E27/ES | R9: | Lamp Dependant |
| MAXIMUM WATTAGE: | 1 x 60W Max | MACADAM ELIPSE: | Not Applicable |
| MAXIMUM LAMP LENGTH: | 95mm | UGR: | Not Applicable |
| LAMP INCLUDED? | No | BEAM ANGLE: | Not Applicable |
| LUMINOUS FLUX: | Lamp Dependant | AVERAGE LIFESPAN: | Lamp Dependant |
| COLOUR TEMP: | Lamp Dependant | L70: | Not Applicable |
| CRI: | Lamp Dependant | | |
| ADDITIONAL LAMP | | | |
| LIGHT SOURCE: | High Power LED | MACADAM ELIPSE: | 3-Step |
| MAXIMUM WATTAGE: | 1 x 1W | UGR: | Not Applicable |
| AMP INCLUDED? | Yes (Integral) | BEAM ANGLE: | To Be Advised |
| LUMINOUS FLUX: | 58(lm) | TILT ADJUSTMENT ANGLE: | 90 (Degrees) |
| COLOUR TEMP: | 2700 (K) | ROTATION ADJUSTMENT ANGLE: | 180 (Degrees) |
| CRI: | 85 | AVERAGE LIFESPAN: | 60,000 (Hrs) |
| R9: | To Be Advised | L70: | To Be Advised |
| ELECTRICAL | | | |
| SWITCHED: | Yes | DRIVER/BALLAST VOLTAGE: | 100-240 (V) |
| DIMMABLE: | No | DRIVER AVERAGE LIFESPAN: | 30,000 (Hrs) |
| DIMMING METHOD: | Not Applicable | MAIN LAMP EFFICACY: | Lamp Dependant |
| DRIVER OUTPUT CURRENT: | 350 (mA) | ADDITIONAL LAMP EFFICACY: | To Be Advised |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER INCLUDED? | Yes (Integral) |
| SUPPLY FREQUENCY: | 50/60 (Hz) | | - |

PRODUCT ELEVATIONS





