KASHIMA 350 LED **7348**

astro

SKU 1174003



PRODUCT SPECIFICATION

GENERAL

FINISH: Polished Chrome CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminum **GROSS WEIGHT:** 1.24 (kg) H: 55mm W: 350mm D: 180mm **DIMENSIONS:** CLASS: CE (Class II) INSTALLATION ORIENTATION: Wall/Cabinet Mount - Horizontal IP RATING: IP44

Not Applicable Zone 2, 3 **CUT OUT HOLE: BATHROOM ZONE: RECESS DEPTH:** Not Applicable VOLTAGE: Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE: Mid-Power LED MACADAM ELIPSE: 3-Step

UGR: MAXIMUM WATTAGE: 3.2W Not Applicable MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** Not Applicable LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** 165.3 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable

COLOUR TEMP: AVERAGE LIFESPAN: 3000 (K) 60,000 (Hrs) CRI: L70: To Be Advised

To Be Advised

ELECTRICAL

R9:

SWITCHED: SUPPLY FREQUENCY: 50/60 (Hz) No DIMMABLE: No DRIVER/BALLAST VOLTAGE: 100-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 30000 (Hrs)

DRIVER OUTPUT CURRENT: 350 (mA) EFFICACY: 36.52 (lm/W) DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable Yes (Integral)

ADDITIONAL INFORMATION



BOX QUANTITY X6

Œ





